

Product Specifications

Style #GPD982



D-ROC®

Magid® D-ROC® AeroDex® 13-Gauge Lightweight Polyurethane Coated Work Glove – Cut Level A9

PRODUCT DESCRIPTION	
Product Classification	Special Purpose Work Glove – Cut Resistant, Coated
Construction/Design	13-gauge, seamless machine knit
Composition	AeroDex® shell; polyurethane palm coating
Color(s)	Blue shell; grey palm coating
Size(s)	5 – 12
Cuff/Finish	Color-coded elasticized overcast: purple (5), grey (6), light blue (7), green (8), red (9), black (10), orange (11), white (12)
Unit of Measure	Pair (must be ordered in multiples of 12 pairs)
Packaging	12 pairs per inner pack, 144 pairs per case

FEATURES & BENEFITS	
<ul style="list-style-type: none">• AeroDex® engineered yarn delivers lightweight A9 cut resistance that is 50% lighter than a traditional HPPE of the same cut level• 13-gauge AeroDex® shell delivers unmatched dexterity & tactile sensitivity making it agile enough for jobs requiring the highest cut protection• AeroDex® is specially engineered to make your hands feel cooler than a comparable cut resistant glove• Lightweight polyurethane palm coating maintains dexterity while delivering excellent grip• Touchscreen compatible to maintain user safety while operating electronic devices• Nitrile reinforced thumb saddle enhances durability at a critical wear point• Shield graphic is color-coded by cut level to easily identify cut protection from a distance• PPG and NEAT Tested• Machine washable for longer service life• ANSI Level A9 Cut Resistance, ANSI Level 5 Abrasion Resistance, ANSI Level 5 Puncture Resistance	

APPLICATIONS

Appliance manufacturing, automotive, construction, glass handling, machining, metal handling, metal stamping, maintenance, assembly, and paper production.

AVAILABLE STYLES

Size	5	6	7	8	9	10	11	12
Item Number	GPD9825	GPD9826	GPD9827	GPD9828	GPD9829	GPD98210	GPD98211	GPD98212

FUNCTIONAL PERFORMANCE

US Standard: ANSI/ISEA 105-2016 American National Standard for Hand Protection Selection Criteria

Test Method	Clause	ANSI Level
ASTM F2992-15 Cut Resistance	-	A9
ASTM D3389-05 Abrasion Resistance (Using H-18 wheel with a 1000 gram load)	-	5
ANSI/ISEA: 105-2011 Puncture Resistance	6.4	5

SERVICE LIFE

The service life of this product will vary depending on the application and type of care administered. This product should be replaced immediately once a critical or major defect (as defined below) is noted.

Critical Defects	Holes/tears
Major Defects	Dimensional or weight nonconformance, discoloration, other fabric defects

LAUNDERING GUIDELINES

Gloves are machine washable using soap or detergent. The recommended water temperature is 35°-40°C/95°-104°F. Air dry or tumble dry with a low temperature setting. Do not use bleach. Do not dry in direct sunlight.

GENERAL INFORMATION

CAUTION – This product is cut and puncture resistant, not cut and puncture proof. Do not use near moving or serrated blades.

Originator	Dana Cornish	Date	5/13/2021	
Revised By	Olivia DeVries	Date	06/01/2022	Revision # 1

Please note: Specifications are subject to change.

Neither this nor any statement made by or on behalf of Magid Glove & Safety herein is a warranty that any product is fit for a particular purpose, and Magid Glove & Safety shall not be liable to anyone with respect to this information.

© Magid Glove & Safety Mfg. Co. LLC. Magid® is a registered trademark of Magid Glove & Safety Mfg. Co. LLC. All other trademarks are the property of their respective owners. This document is the property of Magid Glove & Safety and the information contained herein is proprietary to Magid.

WD